

You are here: [Products](#) » [Heatsinks f.cool](#) » [Profile heatsinks and fluid coolers](#) » [Extruded heatsinks for PCB mounting](#) » [SK 76 ...](#) » [SK 76 50 STS TO 220](#)



▼ Heatsinks f.cool

- ▼ Profile heatsinks and fluid coolers
  - Standard extruded heatsinks
  - Extruded heatsinks for lock-in retaining spring
  - **Extruded heatsinks for PCB mounting**
  - Extruded heatsinks for DC/DC converter
  - Retaining springs for transistors
  - U-Extruded heatsinks
  - Die-cast heatsinks
  - Fin coolers
  - Fluid coolers
  - Aluminium flat-, quadrangular-, angled-, U- and T-profiles
- Heatsinks and active heatsinks for processors
- Board Level heatsinks
- Cooling aggregates
- Accessories for electronic components
- **Cases f.case**
- **Connectors f.con**

Extruded heatsinks for PCB mounting

SK 76 ...

SK 76 50 STS TO 220

32 x 20 mm, for semiconductor-screw on mounting

\*1 = versions with solder pins; \*2 = versions without solder pins; L = solderable pins

Data sheet

add to request



Features

Technical Drawing

Variants

Service

Accessories / related products

way of fixation	transistor screw mounting
width B	32 mm
height	20 mm
plate thickness	4 mm
length	50 mm
thermal resistance $R_{th}$	7 K/W
drilling pattern	TO 220/*1
version	with solder pins
surface	black anodised